

# **Safety Data Sheet** Spartan Chemical Company, Inc.

Revision Date: 30-Jul-2015

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

**Product Name:** 

FREEZER CLEANER FP

**Product Number:** 

3128

Recommended Use: **Uses Advised Against:**  Cleaning agent

For Industrial and Institutional Use Only

Manufacturer/Supplier:

Spartan Chemical Company, Inc.

1110 Spartan Drive

Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak:

CHEMTREC 800-424-9300

## 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Serious Eye Damage/Eye Irritation:

Reproductive Toxicity:

Category 2A Category 1B

Specific Target Organ Toxicity (Single Category 3

Exposure):

Flammable Liquids

Category 3

**GHS Label Elements** 

Signal Word:

Symbols:

Danger



**Hazard Statements:** 

Causes serious eye irritation

May damage fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor.

**Precautionary Statements:** 

-Skin

Revision Date: 30-Jul-2015

Prevention: Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash hands and any exposed skin thoroughly after handling.

Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground container and receiving equipment. Use explosion-proof electrical equipment.

Use only non-sparking tools

Take precautionary measures against static discharge

Wear eve / face protection Wear protective gloves

Response: If exposed or concerned: Get medical attention.

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

-Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. Call a POISON CENTER or doctor/physician if you feel unwell

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information. -Specific Treatment:

In case of fire: Use CO2, dry chemical, or foam for extinction Fire:

Storage: Store locked up. Store in a well-ventilated place, Keep container tightly closed. Keep cool. Disposal: Dispose of contents and container in accordance with local, state and federal regulations,

Hazards Not Otherwise Classified: Not Applicable

Other Information: · Harmful if swallowed

· May cause skin irritation.

· Keep out of reach of children.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
propylene glycol monomethyl ether	107-98-2	30-60
water	7732-18-5	15-40
isopropanol	67-63-0	10-30
2-methoxy-1-propanol	1589-47-5	0.1-1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

-Skin Contact: Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin

irritation occurs: Get medical attention.

-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison control center or physician if you feel unwell.

Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious -Ingestion:

person. Get medical attention if you feel unwell.

Note to Physicians: Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical, CO2, water spray or regular foam, Move containers from fire area if you can

do it without risk

Revision Date: 30-Jul-2015 3128 - FREEZER CLEANER FP

Specific Hazards Arising from the

Chemical:

vapor source. Combustion products are toxic.

flammable. Vapors may travel to areas away from work site before igniting/flashing back to

**Hazardous Combustion Products:** 

May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters: Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective gear. Cool fire-exposed containers with water spray.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Remove all sources of ignition. Avoid contact with skin, eyes or clothing. Use personal

protective equipment as required.

**Environmental Precautions:** Methods for Clean-Up:

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

## 7. HANDLING AND STORAGE

Advice on Safe Handling:

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions:

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
propylene glycol monomethyl ether 107-98-2	STEL: 150 ppm TWA: 100 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m³	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> STEL: 150 ppm STEL: 540 mg/m <sup>3</sup>
isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>

**Engineering Controls:** 

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Skin and Body Protection: Respiratory Protection:

Wear rubber or other chemical-resistant gloves.

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

Revision Date: 30-Jul-2015

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid		
Color:	Clear		
Odor:	Alcohol		
pH:	10.0-11.0		
Melting Point / Freezing Point:	No information available.		
Boiling Point / Boiling Range:	82 °C / 180 °F		
Flash Point:	28 °C / 82 °F ASTM D56		
Evaporation Rate:	< 1		
Flammability (solid, gas)	No information available.		
Upper Flammability Limit:	No information available.		
Lower Flammability Limit:	No information available.		
Vapor Pressure:	No information available.		
Vapor Density:	No information available.		
Specific Gravity:	0.95		
Solubility(ies):	Soluble in water		
Partition Coefficient:	No information available.		
Autoignition Temperature:	No information available.		
Decomposition Temperature:	No information available.		
Viscosity:	No information available.		

## 10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Heat, flames and sparks. Extremes of temperature and direct sunlight.

Incompatible Materials: Strong oxidizing agents. Strong acids.

**Hazardous Decomposition** May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

Products:

#### 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and blurred vision.

-Skin Contact: Drying of the skin.

-Inhalation: Nasal discomfort and coughing. May cause irritation of respiratory tract. May cause

drowsiness or dizziness.

-Ingestion: Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Reproductive Toxicity: May impair fertility. May cause harm to the unborn child. Target Organ Effects: -Eyes. Respiratory System. -Skin. Central nervous system.

**Numerical Measures of Toxicity** 

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 8307 mg/kg ATEmix (dermal): 21635 mg/kg ATEmix (inhalation-dust/mist): 484.3 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
propylene glycol monomethyl ether 107-98-2	= 5200 mg/kg (Rat)	= 13000 mg/kg ( Rabbit )	= 54.6 mg/L (Rat) 4 h > 24 mg/L Rat) 1 h
water 7732-18-5	> 90 mL/kg(Rat)	Not Available	Not Available

3128 - FREEZER CLEANER FP

isopropanol = 4396 mg/kg (Rat) = 12800 mg/kg (Rat) = 72.6 mg/L (Rat) 4 h67-63-0 = 72.6 mg/L (Rat) 4 h

Revision Date: 30-Jul-2015

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
propylene glycol monomethyl ether 107-98-2	Not Available	20.8: 96 h Pimephales promelas g/L LC50 static 4600 - 10000: 96 h Leuciscus idus mg/L LC50 static	Not Available	23300: 48 h Daphnia magna mg/L EC50
isopropanol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	Not Available	13299: 48 h Daphnia magna mg/L EC50

Persistence and Degradability:

Bioaccumulation:

No information available.

No information available.

Other Adverse Effects:

No information available.

#### 13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:

Contaminated Packaging: US EPA Waste Number:

Dispose of in accordance with federal, state and local regulations. Dispose of in accordance with federal, state and local regulations.

D001

## 14. TRANSPORT INFORMATION

DOT:

UN/ID No:

UN 1993

**Proper Shipping Name:** 

Flammable liquids, n.o.s.,(contains isopropanol)

Hazard Class: Packing Group:

III

Special Provisions:

Class 3, Packing Group III materials meet the exception requirements of section 49 CFR 173.150 when individual containers of not more than 1.3 gallons are packed in a strong outer packaging and ground transportation is utilized. Such containers may be reclassified

as "Limited Quantity".

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No:

UN 1993

**Proper Shipping Name:** 

Flammable liquids, n.o.s., (contains isopropanol)

Hazard Class: Packing Group: 3 III

#### 15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### **SARA 313**

This product contains the following listed substances:

isopropanol

CAS No 67-63-0 only if manufactured by the strong acid process, no supplier notification

#### SARA 311/312 Hazard Categories

Acute Health Hazard:
Chronic Health Hazard:
Fire Hazard:
Sudden release of pressure hazard:
No
Reactive Hazard:
No

## California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

## 16. OTHER INFORMATION

Revision Date: 30-Jul-2015

NFPA Health Hazards: 2 Flammability: 2 Instability: 0 Special: N/A

HMIS Health Hazards: 2 Flammability: 2 Physical Hazards: 0

Revision Date: 30-Jul-2015 Reasons for Revision: Section 14 and 15

#### Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**