

## SAFETY DATA SHEET

Revision date 02-Feb-2016

Version 8

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Code

024.0081027

**Product Name** 

QK LOW VOC GARAGE EPOXY KIT DARK BASE

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

## **Section 2: HAZARDS IDENTIFICATION**

## Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 4

#### Label elements



#### Signal word

#### **DANGER**

#### **HAZARD STATEMENTS**

Combustible liquid
Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause cancer

May cause damage to organs through prolonged or repeated exposure

#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

## **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

## Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

#### Skin

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention.

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

#### **STORAGE**

Store locked up. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

## HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

#### **OTHER HAZARDS**

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

## **UNKNOWN ACUTE TOXICITY**

0% of the mixture consists of ingredient(s) of unknown toxicity.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Epoxy Resin	Proprietary	10 - 25
Quartz	14808-60-7	10 - 25
Epoxy Resin	Proprietary	5 - 10
2-Propenenitrile Rxn w/Amino-Trimethylcyclohexanemethanamine	UNKNOWN	3 - 5
Amine Curing Agent	Proprietary	1 - 3

Epoxy Curing Agent	Proprietary	0.3 - 1
Propoxylated Aromatic	9064-13-5	0.3 - 1

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## **Section 4: FIRST AID MEASURES**

#### **First Aid Measures**

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

## Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

#### Skin Contact

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/attention.

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

## Indication of any immediate medical attention and special treatment needed

## **Section 5: FIRE FIGHTING MEASURES**

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

## Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

## Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

## **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

#### For emergency responders

Use personal protection recommended in Section 8.

## **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

#### Methods for containment

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

## **Section 7: HANDLING AND STORAGE**

#### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges.

## **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

## Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Incompatible materials

Bases. Strong bases. Strong oxidizing agents. Strong acids. Acids. Amines.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

## **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Quartz 14808-60-7	TWA: 0.025 mg/m³ respirable fraction	TWA: (30)/(%SiO2 + 2) mg/m³ TWA total dust TWA: (250)/(%SiO2 + 5) mppcf TWA respirable fraction TWA: (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust	
Amine Curing Agent	S* Ceiling: 0.1 mg/m³	TVV/Tespirable fraction	Ceiling: 0.1 mg/m <sup>3</sup>	

## Appropriate engineering controls

## **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

## Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### Thermal Protection

No information available

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Physical state liquid

Appearance No information available

Odor Slight Color white

Odor Threshold
pH value
No information available
No information available
No information available
No information available

Boiling point / boiling range No information available °C / °F

flash point 93 °C / 199 °F

evaporation rate

No information available
Flammability (solid, gas)

No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 9.92 specific gravity 1.19

Solubility(ies)

Partition coefficient

Autoignition temperature

Decomposition temperature

Kinematic viscosity

No information available

Other information

## **Section 10: STABILITY AND REACTIVITY**

**Reactivity** No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous polymerization None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Bases. Strong bases. Strong oxidizing agents. Strong acids. Acids. Amines.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Amines. Chlorine.

## Section 11: TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

Eye contact

Causes serious eye damage

**Skin Contact** 

Causes skin irritation

May cause an allergic skin reaction

Ingestion Not applicable Inhalation

Not applicable

## Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Epoxy Resin	-	-	-
Quartz 14808-60-7	= 500 mg/kg (Rat)	-	-
Epoxy Resin	-	-	-
2-Propenenitrile Rxn w/Amino-Trimethylcyclohexanemeth anamine UNKNOWN	-	-	-
Amine Curing Agent	= 660 mg/kg (Rat)	= 2 g/kg (Rabbit)	= 700 ppm (Rat) 1 h
Epoxy Curing Agent	= 1030 mg/kg (Rat)	-	-
Propoxylated Aromatic 9064-13-5	-	-	-

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 10364 Mg/kg 77522 Mg/kg **ATEmix (dermal)** ATEmix (inhalation-dust/mist) 31.1 mg/l ATEmix (inhalation-vapor) 775 mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chemical Name	ACGIH	<u>IARC</u>	NTP	OSHA
Quartz	A2	Group 1	Known	X
14808-60-7		-		

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen.

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans. NTP (National Toxicology Program)

Known - Known Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Causes skin irritation Serious eye damage/eye irritation Causes serious eye damage Skin sensitization May cause an allergic skin reaction

Respiratory sensitization Not applicable Germ cell mutagenicity Not applicable May cause cancer Carcinogenicity **Reproductive Toxicity** Not applicable Specific target organ toxicity (single Not applicable

exposure)

Specific target organ toxicity

(repeated exposure)

May cause damage to organs through prolonged or repeated exposure

**Aspiration hazard** Not applicable

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity** 

Toxic to aquatic life with long lasting effects.

Environmental precautions Prevent product from entering drains.

Marine pollutant This material meets the definition of a marine pollutant

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects No information available

## Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and Disposal of wastes

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

## Section 14: TRANSPORT INFORMATION

DOT IMDG IATA 14.1 UN/ID no UN1263 UN3082 UN3082

Environmentally hazardous Environmentally hazardous 14.2 Proper shipping name Paint substances, liquid, n.o.s substances, liquid, n.o.s

Bisphenol A-epichlorohydrin Bisphenol A-epichlorohydrin polymer polymer

A97, A158

ALIPHATIC POLYAMINE ALIPHATIC POLYAMINE

COMBUSTIBLE LIQUID 14.3 Hazard Class Ш 14.4 Packing Group

14.5 Environmental hazard Yes

Marine pollutant This material meets the definition of a marine pollutant

Marine pollutant Bisphenol A-epichlorohydrin polymer , ALIPHATIC POLYAMINE 14.6 Special Provisions 274, 335

EmS-No **Emergency Response Guide** 

F-A, S-F Number

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

## **Section 15: REGULATORY INFORMATION**

**International Inventories** 

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing.

Not all components are listed or exempt from listing

## **US Federal Regulations**

## SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardYesFire hazardYesSudden release of pressure hazardNoReactive HazardNo

## **US State Regulations**

## Rule 66 status of product

Not photochemically reactive.

## **California Proposition 65**

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## U.S. EPA Label information

EPA Pesticide registration number Not applicable

## U.S. State Right-to-Know Regulations

Chemical Name
Water
7732-18-5
Epoxy Resin
Quartz
14808-60-7
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Epoxy Resin
2-Propenenitrile Rxn w/Amino-Trimethylcyclohexanemethanamine UNKNOWN
Amine Curing Agent

## **Section 16: OTHER INFORMATION**

#### <u>HMIS</u>

Health hazards
\* = Chronic Health Hazard

Flammability
2
Physical hazards
0
Personal Protection
X

## Supplier Address

Valspar Consumer Headquarters 8725 W. Higgins Rd. Suite 1000

4999 36th St. te Grand Rapids, MI 49512 800-253-3957

The Valspar Corporation

Valspar Plasti-Kote 1636 Shawsone Dr. Mississauga, Ontario L4W 1N7 905-671-8333

Chicago, IL 60631 773-628-5500

Prepared By Product Stewardship

Revision date 02-Feb-2016

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**