

#122

HMIS RATING: 0 HEALTH 2 FLAMMABILITY 0 REACTIVITY
4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT *=CHRONIC HEALTH HAZARD

MATERIAL SAFETY DATA SHEET U.S. DEPARTMENT OF LABOR
COMPLIES WITH USDL SAFETY AND HEALTH REGULATIONS, (29 CFR 1910.1200)

SECTION I: MANUFACTURED BY PRODUCT IDENTIFICATION

CLASSIC PRODUCTS WOOD SOLVE
1 BILOXI SQUARE SOLVENT DEGREASER
WEST COLUMBIA, SC 29170
EMERGENCIES: #803-822-8502

DATE REVISED: 01/10/2012

SECTION II: HAZARDOUS INGREDIENTS CAS # ACGAH TLV/OSHA PEL % OPTIONAL
ALIPHATIC PETROLEUM DIST. 8052-41-3 100 PPM 500 PPM 95 - 99
CITRUS OIL BLEND UNKNOWN UNKNOWN UNKNOWN 1 - 5

DOT HAZARD CLASSIFICATION: COMBUSTIBLE (173,115)
THE EXACT COMPOSITION OF THIS FORMULA IS CONSIDERED TO BE PROPRIETARY
INFORMATION. HOWEVER, THIS PRODUCT CONTAINS NO OTHER HAZARDOUS
COMPONENTS AT A LEVEL OF 1% OR GREATER AND NO KNOWN OR SUSPECTED
CARCINOGEN AT A LEVEL OF 0.1% OR GREATER.

SECTION III: PHYSICAL DATA

BOILING RANGE: 340 DEGREES F. SPECIFIC GRAVITY (WATER=1) 0.76
VAPOR PRESSURE: 2 MMHG @ 20'C. VAPOR DENSITY (AIR=1): 4.9
PERCENT VOLATILE: 100% EVAPORATION RATE (ETHER=1): 70.00
SOLUBILITY IN WATER: NIL PH: NOT APPLICABLE
APPEARANCE AND ODOR: CLEAR LIQUID, FRUIT ODOR

SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): 120' F.
FLAMMABLE LIMITS: LOWER: .7% UPPER:
EXTINGUISHING MEDIA: DRY POWDER; FOAM; CO2.
FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD WEAR SELF CONTAINED
BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER
SPRAY TO COOL NEARBY CONTAINERS AND STRUCTURES EXPOSED TO FIRE.
SPECIAL FIRE & EXPLOSION HAZARD: VAPORS ARE HEAVIER THAN AIR AND MAY
TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED
BY HEAT, PILOT LIGHT OR OTHER FLAMES AT LOCATIONS DISTANT FROM
MATERIAL HANDLING POINT.

SECTION V: HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: NO DATA IS AVAILABLE FOR WOOD SOLVE, HOWEVER ITS LARGEST COMPONENT PETROLEUM DISTILLATE.
 PERMISSIBLE EXPOSURE LIMIT LEVEL: 500 PPM TLV: 100 PPM
 CARCINOGEN: THIS PRODUCT CONTAINS NO KNOWN CARCINOGEN OR POTENTIAL CARCINOGEN AS DEFINED BY OSHA, THE NTP, OR THE IARC MONOGRAPHS.
 EFFECTS OF OVEREXPOSURE:
 EYES: CAN CAUSE SEVERE EYE IRRITATION, REDNESS
 SKIN: DRY SKIN, PROLONGED CONTACT MAY IRRITATE SKIN CAUSING DERMAATITIS.
 EMERGENCY FIRST AID PROCEDURES:
 EYES: FLUSH WITH WATER (MIN 15) IF IRRITATION APPARENT, CALL PHYSICIAN.
 SKIN: FLUSH WITH SOAP & WATER, IF IRRITATION APPARENT, CALL PHYSICIAN
 INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT BREATHING VOMITUS INTO HIS LUNGS.

SECTION VI: REACTIVITY DATA

STABILITY DATA: PRODUCT IS STABLE
 INCOMPATIBILITY: NONE
 HAZARDOUS DECOMPOSITION PRODUCTS: MAY LIBERATE CO, CO2 & UNIDENTIFIED ORGANIC COMPOUNDS IN DENSE BLACK SMOKE.
 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VII: SPILL OR LEAK PROCEDURES

SMALL SPILLS: WIPE UP PRODUCT, RINSE SOILED AREA WITH WATER DOWN DRAIN.
 LARGE SPILLS: STOP LEAK AT THE SOURCE AND COLLECT INTO A SUITABLE CONTAINER, THEN TREAT AS A SMALL SPILL. FOLLOW STATE AND LOCAL REGULATIONS FOR DISPOSAL OF LARGE NON-RECLAIMABLE SPILLS.
 PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: ALWAYS STORE UNUSED PORTION IN ORIGINAL CONTAINER WITH CAP SECURE. AVOID TEMPERATURE EXTREMES.
 OTHER PRECAUTIONS: AS WITH ALL CHEMICALS USE DUE CARE ACCORDING TO LABEL INSTRUCTIONS AND PRECAUTIONS.

SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATOR PROTECTION: WEAR NIOSH-APPROVED RESPIRATOR IN VAPORS OR MIST.
 VENTILATION: LOCAL OR MECHANICAL TO PROVIDE CLEAN WORK ROOM AIR.
 PROTECTIVE GLOVES: FOR PROLONGED USE OR DIRECT CONTACT.
 EYE PROTECTION: CHEMICAL GOGGLES OR FULL FACEPIECE RESPIRATOR.
